

盘形悬式硬质复合绝缘子 Disc Suspension Hard Composite Insulator



盘形悬式硬质复合绝缘子主要尺寸与特性

Main Dimension and Characteristics of Disc Suspension Hard Composite Insulator

序号 Serial Number	产品型号 Product Type	规定机械 抗拉负荷 Specified Mechanical Tensile Pulling Load	绝缘长度 Section Length	最小公称爬电距离 Min nominal Creepage Distance	雷电冲击耐受电压(峰值) 雷电冲击耐受电压 Lightning Impulse Withstand Voltage(Peak Value)	工频耐受电压 Power Frequency Withstand Voltage Test-Dry	工频耐受电压 Power Frequency Withstand Voltage Peak-10h
		kN	H mm	L mm	kV	kV	kV
1	CS120S16BB16-100/450	120	146±4.6	450	100	80	64
2	CS160S20BB20-100/450	160	170±4.6	450	100	80	64
3	FXWP-70	70	146±4.6	400	100	60	30
2	FXWP-120	120	155±4.6	400	100	60	30
3	FXWP-160	120	155±4.6	400	100	60	30

说明：产品的尺寸、特性、连接方式和伞裙颜色等可按客户具体要求设计、生产

Note: Product's dimension, characteristics, connecting type, shed color, etc can be designed and manufactured in accordance with customer's requirements.