

线路保护用复合外套无间隙金属氧化物避雷器产品技术参数 Technical parameters for transmission line used protection of composite housing without gap metal oxide surge arrester product

型号 Type	系统额定电压kV (有效值) System rated voltage kV [Effective value]	额定电压 kVr.m.s Rated Voltage (kVr.m.s)	持续运行电压 kVr.m.s Continuous operating voltage (kVr.m.s)	直流参考电压 ≥kV DC reference voltage <sup>9</sup> (≥kV)	2ms方波电流 A 2ms square wave current A	残压 ≤kVp Residual voltage(≤kVp)			持续电流阻性分量 mA [峰值] Continuous current resistance component mA (peak)
						30/60 μs 陡波冲击 30/60 μs switching impulse	8/20 μs 雷电冲击 8/20 μs lightning impulse	1/10 μs 操作冲击 1/10 μs steep impulse	
YH5WX-17/50W	10	17	13.6	25	100	57.5	50	42.5	0.2
YH5WX-51/134W	35	51	40.8	73	400	154	134	114	0.2
YH10WX-96/250W	66	96	75	140	600	288	250	213	0.3
YH10WX-108/261W	110	108	84	157	600	315	281	239	0.3
YH10WX-114/297W	110	114	89	165	600	341	297	252	0.3
YH10WX-216/562W	220	216	168.5	314	600	630	562	478	0.3
YH10WX-312/760W	330	312	237	442	1000	847	760	643	0.35
YH10WX-324/789W	330	324	246	459	1000	880	789	668	0.35
YH20WX-444/1106W	500	444	324	597	1500	1238	1106	907	0.6
YH20WX-468/1166W	500	468	330	630	1500	1306	1166	956	0.6

变压器中性点用复合外套无间隙金属氧化物避雷器产品技术参数 Technical parameters for transformer neutral point used composite housing without gap metal oxide surge arrester product

型号 Type	系统额定电压kV (有效值) System rated voltage kV [Effective value]	额定电压 kVr.m.s Rated Voltage (kVr.m.s)	持续运行电压 kVr.m.s Continuous operating voltage (kVr.m.s)	直流参考电压 ≥kV DC reference voltage <sup>9</sup> (≥kV)	2ms方波电流 A 2ms square wave current A	残压 ≤kVp Residual voltage(≤kVp)			持续电流阻性分量 mA [峰值] Continuous current resistance component mA (peak)
						8/20 μs 雷电冲击 8/20 μs lightning impulse	1/10 μs 操作冲击 1/10 μs steep impulse	1/10 μs 操作冲击 1/10 μs steep impulse	
YH1.5W-30/80W	35	30	24	44	400	80	75	0.2	
YH1.5W-60/144W	110	60	48	85	400	144	135	0.3	
YH1.5W-72/186W	110	72	58	103	400	186	174	0.3	
YH1.5W-144/320W	220	144	116	205	400	320	299	0.3	
YH1.5W-207/440W	330	207	166	292	600	440	410	0.35	
YH1.5W-102/260W	500	102	82	155	600	260	243	0.6	
YH1.5W-96/260W	500	96	77	137	600	260	243	0.6	

说明：产品的尺寸、特性、连接方式和伞裙颜色等可按照客户具体要求设计、生产  
Note: Product's dimension, characteristics, connecting type, shed color, etc can be designed and manufactured in accordance with customer's requirements.